



## BIT ADD S

- BIT S -

Additive for PMBCs for spray applications

<b>Availability</b>	
Quantity per pallet	432
<b>Size / Quantity</b>	
Type of container	Plastic bottle
Container code	01
<b>Art. no.</b>	
0869	■

Application rate 100 - 300 ml per container



Range of use ■ Working with PMBCs in spray applications

Property profile ■ Solvent-free  
■ Plasticising



Characteristic data of the product

Density of ready-to-use mixture	Approx. 1.00 kg/l
Base	Aqueous solution
Consistency	Liquid

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products  
 > BIT K2 (0888)  
 > BIT 2K <sup>[basic]</sup> (0871)


Directions ■ Conditions for use  
 Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.



Once the mixing process is complete, pour the product into the bitumen and mix thoroughly.

Notes Deviations from applicable regulations must be agreed separately.  
 The relevant test certificates must be observed when planning and carrying out work.

Storage / Shelf life If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



Safety data / Regulations For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Personal protective equipment Respiratory protection with a particle filter P2 must be worn during spraying, together with protective goggles. Wear suitable protective gloves and clothing.



---

## Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.