



## BTM [basic]

### - BTM Universal -

Sprayable, universal release agent based on mineral oils

Availability			
Quantity per pallet	50	24	2
Size / Quantity	10 l	30 l	200 l
Type of container	Tin canister	Tin canister	Drum
Container code	10	30	69
Art. no.	1117	■	■

#### Application rate

Dependent on application and formwork surface  
Non-absorbent formwork: approx. 1 l / 80 m<sup>2</sup>  
Absorbent formwork: approx. 1 l / 40 m<sup>2</sup>



#### Range of use

- Absorbent and non-absorbent formwork substrates
- Heated formwork up to +80 °C
- Protective agent for concrete tables, production facilities and construction machinery



#### Property profile

- Universal use with a wide range of formworks
- Suitable for fair-faced concrete
- Excellent release action, weather-resistant and non-damaging to the formwork
- Application by brush or spraying
- Solvent-free
- Low odour

#### Characteristic data of the product

Density (20 °C)	0.85 g/cm <sup>3</sup>
Flash point °C	> 100
Consistency	Liquid
Colour	Yellowish

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.


#### Certificates

- [Anwendungsübersicht Betontrennmittel \(BTM\)](#)

#### Preparation

- Substrate requirements  
Clean any dirt or wax off the formwork.
- Substrate preparation  
Before using new wooden formwork for the first time, coat with a sufficient quantity of cement paste. Brush off the next day and treat with release agent.

#### Directions



- Conditions for use  
Temperature of the material, air and substrate: from min. +5 °C to max. +80 °C.
- Ready to use, straight from the container.  
Apply a thin layer of the material.  
Make sure that no pools form.

#### Notes

When using on fair-faced concrete surfaces according to the DBV (German Institute for Concrete) data sheet, set up a trial area depending on the fair-faced concrete class.  
Remove all material residue from the concrete surface before applying any coatings.



---

Deviations from applicable regulations must be agreed separately.

---

Tools / Cleaning

Clean tools immediately after use with V 101 Thinner.




Remmers tools

- [Gloria Drucksprüher Pro 100 \(4668\)](#)
- [Gloria CleanMaster PERFORMANCE PF 50 \(4666\)](#)
- [Gloria CleanMaster EXTREME EX 100 \(4665\)](#)

---

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.



---

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

Personal protective equipment

Respiratory protection with at least an A/P2 combination filter must be worn during spraying, together with safety goggles. Wear suitable protective gloves and clothing.

---

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.