Formwork Paste

Brush-on concrete release agent

Availability		
Quantity per pallet	30	14
Size / Quantity	**10 l**	**30 l**
Type of container	Tin bucket	Tin bucket
Container code	10	30
Art. no.		
1121	■	■

Application rate

Non-absorbent formwork: approx. 1 l / 30 - 50 m²



Range of use

- Non-asborbent formwork
- For use in prefabricated components

Property profile

- Universal use with a wide range of formworks
- Excellent release action, weather-resistant and non-damaging to the formwork
- Spreadable

Characteristic data of the product

Density (20 °C)	0.83 g/cm³
Flash point °C	> 60
Consistency	Paste-like
Colour	Whitish

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates

› Anwendungsübersicht Betontrennmittel (BTM)

Preparation

- Substrate requirements
  Clean any dirt or wax off the formwork.

- Substrate preparation
  Before using new wooden formwork for the first time, coat with a sufficient quantity of cement paste. Brush off the next day and treat with release agent.

Directions

- Conditions for use
  Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.

  Ready to use, straight from the container.
  Apply a thin layer of the material.
  Do not let excess material build up on the surface.

Notes

Remove all material residue from the concrete surface before applying any coatings.
Deviations from applicable regulations must be agreed separately.

Tools / Cleaning

Short-bristled broom, flat brush, rubber scraper, cloth
Clean tools immediately after use with V 101 Thinner.

Remmers tools

- Flächenstreicher (4540)
- Farbrolle FC (4913)
- Rollerbügel (4449)
- Epoxy Roller (5045)
- Nylon Roller Standard (5066)
- Heizkörperpinsel (4541)

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.