



Concrete remover

Concrete, mortar and cement skin remover

Availability		
Quantity per pallet	84	24
Size / Quantity	5 kg	30 kg
Type of container	Plastic canister	Plastic canister
Container code	05	30
Art. no.	1211	■

Application rate Apply to a large enough trial area to determine the precise amount required.

Range of use ■ Cleaning construction machinery and formwork

Property profile




- Highly acidic
- Dissolves cementitious impurities and rust films
- Corrosion protection inhibitors
- Economical use thanks to application-specific dilution

Certificates > [Data sheet for constituents](#)

Production of the mixture

Dilute concentrate with water.
Dilution dependent on application: 1:1 to 1:2
Immersion bath: 1:2 to 1:4

Directions



- **Conditions for use**
Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.

Apply the material using suitable equipment.
Remove residue with a stiff brush or a filling knife.
Treat thick layers multiple times wet-on-wet.
Rinse cleaned surfaces with clear water.

Tips on use

Do not allow the substrate to dry out.
Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.
Set up the necessary collection receptacles.

Notes Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.

Tools / Cleaning


Clean tools with water while the material is still fresh.

- Remmers tools
- > [Mischgefäß \(4030\)](#)
- > [Heizkörperpinsel \(4541\)](#)



Storage / Shelf life

At least 36 months in unopened, original containers stored cool, dry and protected from frost.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Personal protective equipment

Respiratory protection with a particle filter P2 must be worn during spraying, together with protective goggles. Wear suitable protective gloves and clothing.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.