



## Thinner & Brush Cleaner


Mixture of de-aromatised solvents

<b>Availability</b>	
Quantity per pallet	540
<b>Size / Quantity</b>	
Type of container	Tin canister
Container code	01
<b>Art. no.</b>	
1345	■

Application rate According to needs

Range of use

- Adjusting the viscosity of solvent-based alkyd resin stains and lacquers
- Cleaning tools
- Cleaning and degreasing substrates



Property profile

- Mild odour
- De-aromatised
- Good cleaning action



Characteristic data of the product

Density (20 °C)	Approx. 0.78/cm <sup>3</sup>
Flash point °C	Approx. 42 °C
Odour	Solvent-like

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Additional information [▶ Data sheet of constituents](#)

Directions

Slowly stir into the lacquer or stain until the desired consistency is reached.  
Seal opened containers well and use contents as soon as possible.

Tips on use

Check compatibility with the substrate.

Tools / Cleaning

Remove spilled thinner immediately using a cleaning rag. Collect and dispose of rags in fire-proof waste containers.

Storage / Shelf life

Unlimited



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Detergents Regulation (EC) No  
648/2004

5-10% (2-methoxymethylethoxy)propanol  
< 95% aliphatic hydrocarbons

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.