



## Maintenance Primer

Special primer for lightening weathered and greyed woods




Colour	Availability		
	Quantity per pallet	672	200
	<b>Size / Quantity</b>	<b>3 x 0,75 l</b>	<b>2 x 2,5 l</b>
	Type of container	Tin bucket	Tin bucket
	Container code	01	03
	<b>Art. no.</b>		
spruce	1504	■	■

### Application rate

Approx. 100 ml/m<sup>2</sup> depending on the absorbency of the wood



### Range of use



- For use on interior and exterior wood
- Dimensionally stable wood building elements: e.g. windows and doors
- Wood building elements with limited dimensional stability, e.g. folding shutters, matchboarding, summerhouses
- Wood building elements with no dimensional stability: e.g. fences, framework, carports, planking
- Maintenance and levelling of greyed and spotted wood surfaces
- Not suitable for coating flooring (terraces, wooden decking, etc.)

### Property profile



- Weatherproof and moisture-regulating
- Quick drying
- Good coverage with just one coat
- Very good adhesion to the substrate

### Characteristic data of the product

Binder	Acrylate/alkyd system
Density (20 °C)	1.07 g/cm <sup>3</sup>
Odour	Mild

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Additional information

➤ [Nachhaltigkeitsdatenblatt](#)

### Possible system products

- [Wood Preservative Primer\\* \(2066\)](#)
- [Long Life Stain UV \(2234\)](#)

\*Use biocidal products carefully.

Always read the label and product information before use.

### Preparation

- **Substrate requirements**  
Dimensionally stable wood building elements: wood moisture content 11-15%  
Wood building elements with limited or no dimensional stability: wood moisture content max. 18%
- **Substrate preparation**  
Thoroughly remove any dirt, grease and non-adhering old coatings.  
Using a brass brush, thoroughly clean greyed and weathered wood surfaces to ensure optimum adhesion.



Remove loose and torn knots as well as resin that bleeds and clean with a suitable product (e.g. Remmers thinner & brush cleaner).  
Exterior wood that needs to be protected against soft rot and blue stain must be pre-treated with a suitable wood preservative\* (\*Use biocides safely. Always read the label and product information before use).  
Round off sharp edges.  
Observe BFS Code of Practice No. 18 "Coatings on Wood and Wooden Working Materials in Outdoor Areas".

## Directions



### ■ Conditions for use

Temperature of the material, air and substrate: from min. +5 °C to max. +25 °C.

Stir well.

Apply by brush.

Apply in the direction of the grain.

After drying, apply the intermediate and final coats of LT Stain UV.

Seal opened containers well and use contents as soon as possible.

## Tips on use



Check colour, adhesion and compatibility with the substrate by setting up a trial area.

Before coating technically modified woods and wood-based materials, apply the product to a trial surface and conduct a suitability test on the desired area of use.

When renovating windows and exterior doors, we recommend an intermediate sanding step using sandpaper (P180) or a fine sanding sponge prior to further coating.

### ■ Drying

Can be overcoated: after approx. 4 hours

Practice values at +20 °C and 65% relative humidity.

Low temperatures, poor ventilation and high humidity delay drying.

### ■ Thinning

Ready to use

## Notes

Observe the regulations concerning design principles for wood protection.

Do not use on horizontal surfaces without drainage slopes and without edge radius, avoid accumulated moisture.

## Tools / Cleaning



Brush with synthetic bristles, flat brush

Clean tools immediately after use with water and detergent.

Ensure that any residue from cleaning is disposed of correctly.

## Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

Use the contents of open containers as quickly as possible.

## Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

## Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

## Biocidal Products Regulation

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

## VOC content as per the "Decopaint" Directive (2004/42/EC)

EU limit value for the product (Cat. A/e): max. 130 g/l (2010).  
This product contains < 130 g/l VOC.





Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.