



Induline GLF-925 Glazing Bar Filler

Alkoxy-crosslinking silicone sealant



Colour	Availability
	Quantity per pallet 864
	Size / Quantity 12 x 600 ml
	Type of container aluminium bag
	Container code 60
	Art. no.
black grey	021529 ■

Application rate Approx. 25 ml/running metre for a 0.25 cm² joint cross-section



Range of use



- Dimensionally stable wood building elements: e.g. windows and doors
- Waterproofing and backfilling of window casement frames and glazing bars
- For use by professionals

Property profile

- Protects against condensation in the glazing rebate
- Reduces heat loss by sealing off the glazing rebate
- Optimised adhesion profile for easy removal of glazing bars
- Permanently elastic
- Coating-compatible according to DIN 52452, part 4
- Easy to apply
- Tested compatibility with commonly used materials: edge compound, glazing packers, laminated glass
- Colour-matched to the edge compound
- Very low emissions (GEV-EMICODE EC 1^{PLUS})
- Complies with the principles for the health assessment of construction products used indoors (AgBB scheme)

Characteristic data of the product

Density (20 °C)	Approx. 1.5 g/ml
Viscosity	Paste-like/stable

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates > [Prüfbericht GEV Emicode](#)

Additional information > [Compatibility list](#)


Possible system products > [MultiSil \(7380\)](#)
> [Induline window coating system](#)

Preparation

- **Substrate requirements**
The substrate must be clean, dry, free of dust, grease and loose substances, and prepared in the correct manner.
- **Substrate preparation**
Compatibility with the materials used must be ensured. Please refer to the compatibility list. Contact Remmers Technical Service if necessary.



Directions



Conditions for use

Temperature of the material, air and substrate: from min. +5 °C to max. +35 °C.

Cut off tip at an angle according to the width of the joint and inject, filling the joint completely. Apply to the joint edges using sufficient pressure.

Notes

Observe the regulations of Code of Practice No. 10 from the "Industrieverband Dichtstoffe" (Association of the Sealants Industry, IVD).

Not suitable for sealing glazing rebates.

Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately.

The relevant test certificates must be observed when planning and carrying out work.


Tools / Cleaning

Manual and compressed-air gun



Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.