



Aqua V-490-Retarder

Retarder to improve flow

Availability	
Quantity per pallet	432
Size / Quantity	
Type of container	Tin canister
Container code	01
Art. no.	
1939	■

Application rate
Add 5 - 10% to Aqua stains
Add 1 - 3% to Remmers Aqua varnishes

Range of use



- Brush, roller or spray application of 1K Aqua varnishes
- Spray application of 2K Aqua varnishes
- In low humidity: flow improver for Aqua varnishes
- On absorbent wood types: modifying the properties of Aqua stains
- For use by professionals

Property profile



- Extends the open time (Aqua varnishes or stains)

Characteristic data of the product


Density (20 °C)	Approx. 0.92 g/cm ³
Odour	Characteristic

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- Aqua KB-004 Compact Stain (3840)
- Aqua TL-412 Stair Varnish (2372)
- Aqua 2HL-411/90-2K High Gloss Varnish (3872)
- Aqua CL-440 Colour Opaque (3802)
- Aqua PL-413 Parquet Varnish (2374)
- Aqua SL-414 Finish (3820)

Directions



- **Conditions for use**
Temperature of the material, air and substrate: from min. +15 °C to max. +25 °C.
- Mix the product 1:1 with water and add to the varnish while stirring.
- Seal opened containers well and use contents as soon as possible.

Tips on use

- **Thinning**
1:1 with water

Notes

The product can be used to adjust the viscosity of the varnish.

Tools / Cleaning




Remmers Patent Disperser
Clean tools with water or Aqua RK-898 Cleaning Concentrate immediately after use.
Ensure that any residue from cleaning is disposed of correctly.



Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.