




SM-820 Texturing Agent

Additive for producing textured coatings

Colour	Availability	
	Quantity per pallet	200
	Size / Quantity	0,5 kg
	Type of container	Plastic bucket
	Container code	01
	Art. no.	
SM-820/S Texturing Agent fine	1942	■
SM-820/M Texturing Agent medium	1943	■
SM-820/L Texturing Agent coarse	1944	■

Range of use



- For creating texture varnishes
- PUR varnishes and Aqua varnishes
- For use in glass varnishes
- Can be used on floors to improve slip resistance
- For use by professionals

Property profile

- Creates a rough feel
- Elevated resistance
- Creates a matt appearance
- Can be used on floors and stairs to improve slip resistance
- Easy to use thanks to enclosed dispenser and easy application


Characteristic data of the product

Odour	Odourless
The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.	

Possible system products

- Aqua TL-412 Stair Varnish (2372)
- Aqua PL-413 Parquet Varnish (2374)
- PUR SL-21X Finish
- PUR CL-24X colour varnishes
- Aqua SL-41X Finish
- PUR BML-215 Brilliant Matt Lacquer (1941)
- Aqua 2DS-450-2K Diamond Seal (3869)

Production of the mixture



Mixing ratio

Approx. 100 ml (40 g) per litre of ready-to-use varnish

Use the enclosed mixing container for precise dispensing.
Using the Patent Dispenser, work into the coating material while stirring.
No need to pre-mix with thinner or water.
Adjust the coating material to achieve a workable viscosity if necessary.

Directions

- Conditions for use
See the Technical Data Sheet for the coating material used.

Seal opened containers well and use contents as soon as possible.


Tips on use

Check colour, adhesion and compatibility with the substrate by setting up a trial area.



Storage / Shelf life

At least 60 months in unopened, original containers stored cool, dry and protected from frost.



Personal protective equipment

Respiratory protection with a particle filter P2 must be worn during spraying, together with protective goggles. Wear suitable protective gloves and clothing.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.