



PUR GLA-820 Glass Lacquer Additive

Additive for improving the adhesion of PUR lacquers on glass

Colour	Availability	
	Quantity per pallet	200
	Size / Quantity	0,5 l
	Type of container	Tin canister
	Container code	01
	Art. no.	
	1946	■

Range of use



- Coloured designs on the rear face of glass surfaces
- Furniture building and shop fitting
- Can be used with a wide range of Remmers PUR lacquers
- For use by professionals

Property profile



- Significant improvement in adhesion of lacquer on glass
- Cost-effective alternative also suitable for small production runs
- Easy to use


Possible system products

- SM-820 Texturing Agent (1942)
- MultiSil (7380)
- PUR BML-215 Brilliant Matt Lacquer (1941)
- PUR SL-21X Finish
- PUR CL-24X colour varnishes

Preparation

- Substrate requirements
The substrate must be clean, dry, free of dust, grease and loose substances, and prepared in the correct manner.

Production of the mixture



[ZB_HB_54]
Using the Patent Disperser, work into the coating material while stirring.
Processing time for PUR varnishes is reduced by approx. 50%.


Directions

- Conditions for use
See the Technical Data Sheet for the coating material used.
- Seal opened containers well and use contents as soon as possible.

Tips on use

Check colour, adhesion and compatibility with the substrate by setting up a trial area.

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 6 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal



Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.