



UN-894-Umnetzer

Availability	
Quantity per pallet	96
Size / Quantity	
Type of container	Tin canister
Container code	05
Art. no.	
1947	■

Range of use



- Cleaning spraying equipment
- Cleaning solvent-resistant surfaces (e.g. glass)
- Degreasing surfaces
- For thorough cleaning of wooden floors
- For use by professionals

Property profile



- Good cleaning action
- Compatible with water-based and solvent-based products


Directions

Changing from solvent-based to water-based varnishes: Clean coating equipment, including filter inserts, with WV-891 or V-890. Then thoroughly rinse with UN-894 and then with water.
Changing from water-based to solvent-based varnishes: Clean coating equipment, including filter inserts, with water and with an Aqua RK-898 solution if necessary. Then thoroughly rinse with UN-894 and then with WV-891 or V-890.

Tips on use

Can be left in unused spraying equipment.

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.