



Aqua FKL-402 Joint Filler Liquid

Water-based joint filler liquid for parquet and wooden flooring

Colour	Availability
	Quantity per pallet 96
	Size / Quantity 51
	Type of container Plastic canister
	Container code 05
	Art. no.
clear	2368 ■


Application rate

Approx. 50 ml/m²

Actual application rate: dependent on the nature of the floor/joints.



Range of use



- Interior wood
- Filling parquet and wooden floors
- For use by professionals

Property profile



- Low volume shrinkage
- Low solvent, mild odour
- Quick-drying

Characteristic data of the product

Density (20 °C)	1.04 g/m ³
Viscosity	Liquid
Odour	Mild
Colour	Milky, transparent once dry

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Additional information

- [Sustainability Data Sheet](#)

Possible system products

- [Aqua PL-413 Parquet Varnish \(2374\)](#)
- [HWS-112 Hard Wax Seal \(1826\)](#)
- [HSO-118 High Solid Oil ^{\[eco\]} \(7708\)](#)
- [Aqua HWS-712 Hard Wax Seal ^{\[eco\]} \(5290\)](#)

Preparation

■ Substrate requirements

The substrate must be clean, dry, free of dust, grease and loose substances, and prepared in the correct manner.

Joint width should not be larger than 1 mm.

Production of the mixture


■ Mixing

Mixed with 10-20% wood flour from final sanding to create a compound that can be used for filling. Working time max. 10 min; this may be lower at high temperatures.





Directions



■ **Conditions for use**

Temperature of the material, air and substrate: from min. +15 °C to max. +25 °C.

Shake well before use.
 Apply with a smoothing spatula before final sanding.
 Carry out final sanding once dry.
 Repeat the process if necessary.
 Then apply your chosen system product for wood treatment.
 Seal opened containers well and use contents as soon as possible.

Tips on use



Check colour, adhesion and compatibility with the substrate by setting up a trial area.
 Joints and cracks wider than 1 mm cannot be permanently closed with the joint filler.

■ **Drying**

Ready for overcoating: after approx. 45 - 60 minutes
 Practice values at +20 °C and 65% relative humidity.

■ **Thinning**

Ready to use

Tools / Cleaning




Flexible scraper

Clean tools immediately after use with water and detergent.
 Tools must be free of rust.

Remmers tools

➤ **Federspachtel (4788)**

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Biocidal Products Regulation

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.