



## Aqua MSV-403 Parquet Primer


Special primer for parquet and wooden flooring, minimises unwanted adhesion

Colour	Availability	
	Quantity per pallet	96
	<b>Size / Quantity</b>	<b>5 l</b>
	Type of container	Plastic canister
	Container code	05
	<b>Art. no.</b>	
clear	2369	■

**Application rate** 100 - 120 ml/m<sup>2</sup> per coat



### Range of use



- Interior wood
- Industrial parquet
- Wooden strip flooring
- Parquet without shear resistance
- Wood block flooring
- Heated floors
- For use by professionals

### Property profile



- Minimises unwanted adhesion caused by material running into joints
- Reduces the risk of joint fractures
- Good sanding properties

### Characteristic data of the product

Binder	Acrylate
Density (20 °C)	Approx. 1.03 g/cm <sup>3</sup>
Runout time s in DIN 2 cup	Approx. 55
Odour	Mild

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Additional information

- [Sustainability data sheet](#)

### Possible system products


- [Aqua PL-413 Parquet Varnish \(2374\)](#)
- [Aqua V-490-Retarder \(1939\)](#)

### Preparation

- **Substrate requirements**  
The substrate must be clean, dry, free of dust, grease and loose substances, and prepared in the correct manner.  
Wood moisture content: 8-12%
- **Substrate preparation**  
Sand wood with P 80 - 150.



**Directions**



■ **Conditions for use**

Temperature of the material, air and substrate: from min. +18 °C to max. +25 °C.

Shake well before use.

Apply with a roller.

Intermediate and final coats of suitable products can be applied after drying.

When allowed to dry overnight, intermediate sanding is required.

Seal opened containers well and use contents as soon as possible.

**Tips on use**



Check colour, adhesion and compatibility with the substrate by setting up a trial area.

Do not empty and disperse on the floor (material build-up).

■ **Drying**

Overcoating: after approx. 1-2 hours

Practice values at +20 °C and 65% relative humidity.

Low temperatures, poor ventilation and high humidity delay drying.

■ **Thinning**

Ready to use

**Tools / Cleaning**



Rustproof tools

Sealant roller with microfibre cover, pile height approx. 8-12 mm


[GR\_RA\_1]

[GR\_V\_2]

Clean tools with water or Aqua RK-898 Cleaning Concentrate immediately after use.

Ensure that any residue from cleaning is disposed of correctly.

**Storage / Shelf life**



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

**VOC content as per the "Decopaint" Directive (2004/42/EC)**

EU limit value for the product (cat A/i): max. 140 g/l (2010).

This product contains < 140 g/l VOC.

VOC	
Kat.	A/i
2010:	140g/l
max.:	140g/l

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.