



Directions



■ **Conditions for use**

Temperature of the material, air and substrate: from min. +5 °C to max. +25 °C.

Use the special scrubbing brush, a surface brush or paintbrush to apply a generous, even layer of material to the entire area.

Leave the material to take effect for approx. 15 minutes.

Keep the treated area damp during this time.

Scrub down the wood in the direction of the grain/board by board using the special scrubbing brush.

Hose down the wood thoroughly.

Keep rinsing until no more foam forms. It may help to use a coarse broom to sweep away residual water.

No white product residue can be allowed to remain.

Repeat the process if dealing with heavily greyed substrates.

After leaving to dry for 1-2 days, re-treat using garden wood oils, maintenance oils or WPC impregnating oils.

Wood surfaces that have become heavily roughed up can be smoothed down in advance with sandpaper if necessary.

Seal opened containers well and use contents as soon as possible.

Tips on use

Always set up a trial area/trial areas first.

Rinse treated areas with plenty of water.

Try not to let any cleaning or rinsing water get into bodies of water or gardens. Protect them against direct contact using a sheet or tarpaulin where necessary.

Check colour, adhesion and compatibility with the substrate by setting up a trial area.

Tools / Cleaning




Special scrubbing brush, paintbrush with synthetic bristles, flat brush

Clean tools immediately after use with water.

Ensure that any residue from cleaning is disposed of correctly.

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Detergents Regulation (EC) No 648/2004

< 5% oxalic acid

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.