



## Door Care Kit

For painted and stained front doors




Availability	
Quantity per pallet	500
Size / Quantity	Unit
Type of container	Set in carton
Container code	01
Art. no.	
2746	■
The kit contains: 250 ml cleaner, 250 ml wood balm and 2 special cloths	

**Application rate** 5 - 10 ml/m<sup>2</sup> per coat



### Range of use



- Maintenance of painted and stained wooden front doors
- Maintenance of components that have been treated with Induline NW-740/05 (natural effect varnish)

### Property profile

- Regular use increases the time between maintenance intervals and extends the lifespan of the surfaces
- Additional protection against the effects of weathering
- Easy to use on large surface areas
- Slight change in the gloss level of the treated surface

### Characteristic data of the product


Runout time s (20° C, ISO 3)	Approx. 22 - 25
Density (20 °C)	Approx. 0.98 g/cm <sup>3</sup> (Cleaner for Care Kits) Approx. 1.00 g/cm <sup>3</sup> (Wood Balm for Doors)
Odour	Characteristic (Cleaner for Care Kits) Mild (Wood Balm for Doors)

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Certificates

- **Remmers International Guarantee**  
Inasmuch as a Remmers International Guarantee (RIG) has been granted, only the conditions / requirements indicated in the written contract between die RIG specialist firm and Remmers shall apply.

### Directions



#### Conditions for use

Temperature of the material, air and substrate: from min. +15 °C to max. +25 °C.

Shake well before use.

Wear gloves (nitrile rubber).

Soak a cotton cloth with the cleaner and clean the surface; do not rub painted surfaces too intensively.

Leave to dry for approx. 30 minutes.

Using the second special cloth, apply a thin(!) layer of balm quickly, evenly and in one direction (left to right or top to bottom).

Do not buff or rub.



**Tips on use**



Protect freshly treated surfaces from driving rain, wind, sunlight and condensation.

Do not use on areas directly exposed to sunlight or on heated surfaces.

Do not use at temperatures below 15 °C.

Please only use the special cloths enclosed.

Any material that is not made of wood (e.g. covers, glass, door handles) must not come into contact with the cleaning product. If contact does occur, the material should be rinsed carefully with water.

■ **Drying**

Approx. 30 minutes


Practice values at +20 °C and 65% relative humidity.

The coating may take significantly longer to dry thoroughly in lower temperatures, at high humidity or if the maximum layer thickness has been exceeded.

■ **Thinning**

Ready to use

**Storage / Shelf life**



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Detergents Regulation (EC) No 648/2004

<5% non-ionic surfactants, benzisothiazolinone, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)

VOC content as per the "Decopaint" Directive (2004/42/EC)

Wood Balm for Doors:

EU limit value for the product (Cat. A/e): max. 130 g/l (2010).

This product contains < 130 g/l VOC.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.