



# Estrich Schnellzement

Colour	Availability	
	Quantity per pallet	40
	Packaging unit	25 kg
	Type of container	Paper bag
	Container code	25
	Art. no.	
	2814	■

## Range of use



- [AW\_M\_605]
- Screeds on separation layers
- Heated screeds

## Property profile

- [EG\_M\_225]
- [EG\_M\_226]
- Rapid water binding
- Resistant to water, frost and weathering

## Preparation


- **Substrate requirements**  
Clean, dust-free and capable of supporting a load.
- **Substrate preparation**  
[U2\_M\_68]

## Production of the mixture



- **Mixing**  
Pour water into a clean container and add dry mortar.  
Mix thoroughly with a mixer for approx. 3 minutes until homogeneous.  
[VA1\_M\_633]

## Directions



- **Conditions for use**  
Low temperatures increase, while high temperatures decrease the working and setting time.

**Machine working**  
[VA1\_M\_634]

[VA1\_M\_635]

[VA1\_M\_636]



[VA1\_M\_637]

[VA1\_M\_638]

[VA1\_M\_639]

[VA1\_M\_640]

[VA1\_M\_641]

[VA1\_M\_642]

[VA1\_M\_643]

[VA1\_M\_644]

[VA1\_M\_645]

**Tips on use**

Once it has hardened, mortar must not be made workable again by adding either water or more wet mortar.

[VA2\_M\_555]

[VA2\_M\_556]

**Notes**

Low chromate content in accordance with Directive 2003/53/EC.

The characteristic data of the product were calculated under laboratory conditions at 20°C and 65% relative humidity.

The mixing water must be of drinking water quality.

Deviations from applicable regulations must be agreed separately.

The relevant test certificates must be observed when planning and carrying out work.


**Tools / Cleaning**

Clean tools with water while the material is still fresh.



**Storage / Shelf life**

If stored in an unopened container and in a dry place, the product will keep for approx. 12 months.



**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.