



Induline GW-311

Water-based, decorative low-build stain for interior and exterior wood building elements




Type/Name	Availability
	Quantity per pallet 22
	Size / Quantity 20 l
	Type of container Tin bucket
	Container code 20
	Art. no.
clear	283466 ■
special colours	283472 ■

Application rate 80 - 120 ml/m² per coat



Range of use



- For use on interior and exterior wood
- Soft and hard woods
- Building elements with no or limited dimensional stability
- Not for use on floors
- For use by professionals

Property profile



- Quick drying: 2 coats can be applied in one day
- Breathable
- Does not flake
- Repels water
- Pleasant feel
- Uniform varnished finish
- The clear variant does not protect against UV radiation (grey discolouration)

Characteristic data of the product

Density (20 °C)	Approx. 1.01 g/cm ³
Runout time s in DIN 4 cup	Approx. 10-12
Odour	Characteristic

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Additional information

- [Pflege und Wartung von Tauchbecken](#)
- [Hinweise zur Betriebshygiene](#)

Possible system products

- [Induline SW-900* \(3776\)](#)
- *Use biocidal products carefully.
Always read the label and product information before use.

Preparation

- Substrate requirements
- The substrate must be clean, dry, free of dust, grease and loose substances, and prepared in the correct manner.
Wood building elements with limited or no dimensional stability: wood moisture content max. 18%



<div>■ Substrate preparation</div> <p>If necessary, impregnate non-resistant woods with a wood preservative* (*Use biocides safely. Always read the label and product information before use).</p>	
<div>Directions</div> <div></div>	<p>Stir well, including during application or after a break in work. Application by brush, dipping, flow coating, spraying. Industrial series production (VACUMAT® vacuum processing, brushing equipment) Apply the second coat after 2-3 hours. A third coat is recommended on particularly exposed surfaces. When allowed to dry overnight, intermediate sanding is required. Seal opened containers well and use contents as soon as possible.</p>
<div>Tips on use</div> <div></div>	<p>Check colour, adhesion and compatibility with the substrate by setting up a trial area. Ensure good ventilation. Observe the information sheets “Upkeep and Maintenance of Dipping Tanks and Flow Coating Facilities” and “Information on Workplace Hygiene”.</p> <div>■ Drying</div> <p>Ready for next coat: after approx. 2.5 hours Practice values at +20 °C and 65% relative humidity. Low temperatures, poor ventilation and high humidity delay drying.</p> <div>■ Thinning</div> <p>Ready to use</p>
<div>Notes</div>	<p>On planed larch and softwoods with a high resin content, the coating may have reduced adhesion and resistance to weathering. This is especially the case on horizontal year rings, knots and areas of winter growth that are high in resin. Maintenance and renovation must be carried out more frequently on these surfaces. The only remedy for this is pre-weathering or very coarse sanding (P80). If these wood types are rough-sawn, considerably longer maintenance and renovation intervals are to be expected. Observe the information sheets “Upkeep and Maintenance of Dipping Tanks and Flow Coating Facilities” and “Information on Workplace Hygiene”.</p>
<div>Tools / Cleaning</div> <div></div>	<p>Brush, sprayer, dipping tank, flow coating equipment, vacuum processing equipment, brushing machine</p> <p>Clean tools with water or Aqua RK-898 Cleaning Concentrate immediately after use. Ensure that any residue from cleaning is disposed of correctly.</p>
<div>Storage / Shelf life</div> <div></div>	<p>If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.</p>
<div>Safety data / Regulations</div>	<p>For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.</p>
<div>Disposal</div>	<p>Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.</p>
<div>Biocidal Products Regulation</div>	<p>*Use biocidal products carefully. Always read the label and product information before use.</p>
<div>VOC content as per the "Decopaint" Directive (2004/42/EC)</div>	<p>EU limit value for the product (Cat. A/e): max. 130 g/l (2010). This product contains < 130 g/l VOC.</p>

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.