



## Color SP

- Paint for renovation render -

Highly water vapour permeable interior paint for renovation render systems



Colour	Availability		
	Quantity per pallet	48	32
	<b>Size / Quantity</b>	<b>5 l</b>	<b>12,5 l</b>
	Type of container	Plastic bucket	Plastic bucket
	Container code	05	13
	<b>Art. no.</b>		
white	3080	■	■
special colour	3081	■	■

### Application rate

Approx. 0.13 - 0.15 l/m<sup>2</sup> per coat

Application rates may vary depending on the condition of the surface.

Apply to a large enough trial area to determine the precise amount required.



### Range of use

- Opaque coating for repair plaster in indoor areas
- Mineral substrates
- Refurbishing coating on old, solid, matt paint
- Wall paper/ woodchip wallpaper



### Property profile

- Free from solvents and plasticizers
- Low emissions
- Wet abrasion resistance class 3 according to DIN EN 13300
- Hiding power class 1 at 7.5 m<sup>2</sup>/l
- Degree of gloss: dull matt
- Highly permeable to water vapour



### Characteristic data of the product

Binder	Solvent-free acrylate dispersion
Density (20 °C)	Approx. 1.4 kg/l
Viscosity	Ready to use
Water vapour permeability	s <sub>d</sub> value < 0.01 m at 0.3 l/m <sup>2</sup>

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Possible system products


- [Primer Hydro F \(2842\)](#)

### Preparation

- Substrate requirements  
Dry, clean, free of dust and cracks and capable of supporting a load.  
Free of salts known to be damaging to building materials.
- Substrate preparation  
Remove any old coatings not capable of supporting a load, making sure not to leave any residue.  
Prime sanding, well adhering substrates with Primer Hydro F (art. 2842).



#### Directions



#### ■ Conditions for use

Temperature of the material, air and substrate: from min. +5 °C to max. +25 °C.

Stir well.

Coat the surface using a suitable tool.

Depending on the conditions of the substrate, apply 1 or 2 coats.

Wait at least 8 hours between coats.

#### Tips on use

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.

When coating continuous surfaces, only use materials with the same batch number.

Intensive colours, such as yellow, red, etc. may have a lower hiding power due to their pigments. Apply an additional coat if required.

#### Notes

Deviations from applicable regulations must be agreed separately.

The relevant test certificates must be observed when planning and carrying out work.

Always set up a trial area/trial areas first.

#### Tools / Cleaning



Paintbrush, flat brush, lambskin roller, airless sprayer

Clean tools, equipment and any splashed material immediately with water while still fresh.

Remmers tools

- [Collomix® stirrer LX \(4296\)](#)
- [Farbrolle FC \(4913\)](#)
- [Flächenstreicher \(4540\)](#)
- [Heizkörperpinsel \(4541\)](#)

#### Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

#### Personal protective equipment

Respiratory protection with a particle filter P2 must be worn during spraying, together with protective goggles. Wear suitable protective gloves and clothing.

#### Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

#### VOC content as per the "Decopaint" Directive (2004/42/EC)

EU limit value for the product (Cat. A/a): max. 30 g/l (2010).

This product contains < 30 g/l VOC.

VOC	
Kat.	A/a
2010:	30g/l
max.:	30g/l

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.