





# Aqua VGA-485 Cross-Linking Agent & Glass Lacquer Additive

Improves the resistance and adhesion to glass of selected 1K Aqua lacquers



Availability		
Quantity per pallet	880	444
Size / Quantity	0,5 l	11
Type of container	Tin bucket	Tin canister
Container code	84	01
Art. no.		
3256	•	

#### Range of use





Preparation of glass lacquers

- Coloured designs on the rear face of glass surfaces
- Improving the resistance of the lacquer
- Furniture building and shop fitting
- In selected 1K Aqua varnishes
- For use by professionals

### Property profile



- 2K ready: improves the resistance to chemicals, scratches and abrasion of selected 1K varnishes
- Significant improvement in adhesion of lacquer on glass
- Isocyanate-free
- Easy to use
- No pot life (the lacquer regains its 1K properties after 8 hours)

# Characteristic data of the product

ol .

Density (20 °C)

Approx. 1.01 g/cm<sup>3</sup>

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

#### Additional information

> Verarbeitungshinweise 2K-Ready Aqua Lacksysteme

#### Possible system products

- Aqua SL-418 Finish (5310)
- > Aqua NEL-419/05 Natural Effect Varnish (5309)
- Aqua TL-412 Stair Varnish (2372)
- Aqua PF-430 Pigment & Sealing Filler [iac] (3265)
- > Aqua CL-440 Colour Opaque (3802)
- Aqua CL-445 Colour Opaque 4 in 1 (3796)
- > SM-820 Texturing Agent (1942)

#### Preparation

Substrate requirements

The substrate must be clean, dry, free of dust, grease and loose substances, and prepared in the correct manner.

#### Production of the mixture







## Mixing ratio

2% with the ready-to-use lacquer

Using the Patent Disperser, work into the coating material while stirring. The mixture is active for 8 hours.

#### Directions

Conditions for use

See the Technical Data Sheet for the coating material used.

Seal opened containers well and use contents as soon as possible.





Tips on use	Check colour, adhesion and compatibility with the substrate by setting up a trial area.	
Storage / Shelf life	If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.	
Safety data / Regulations	For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.	
Personal protective equipment	Respiratory protection with at least an A/P2 combination filter must be worn during spraying, together with safety goggles. Wear suitable protective gloves and clothing.	
Disposal	Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.	

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.