



# Induline Fast Filler

Dispersion-based 1K-filler

Colour	Availability	
	Quantity per pallet	960
	<b>Size / Quantity</b>	<b>0,4 kg</b>
	Container code	02
	<b>Art. no.</b>	
	3260	■

Application rate As required

Range of use



- Repair work
- Preparation of painting works on wood, wooden materials and mineral Substrates.
- For filling porous substrates and voids.
- For use by professionals

Property profile



- Quick drying at low shrinkage
- Easy to sand
- Good filling performance
- Solvent-free and environmentally friendly

Characteristic data of the product

Density	1.8 g/ml
pH value	Approx. 8
Appearance	White, firm paste

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Directions



- Conditions for use  
Temperature of the material, air and substrate: min. +5 °C.

Clean voids and fill in the product with light pressure with a Japan spatula.  
Refill larger voids after a drying time of approx. 3 hours.  
Maximum layer thickness is 3 mm per application.

Tips on use

To be used outdoors only with the correspondent resistant coating.  
Test unknown coating systems for incompatibility.  
Not suitable for areas which are prone to corrosion.

- Drying  
Drying time: approx. 30 minutes  
Can be sanded/coated: after approx. 3 hours  
Low temperatures, poor ventilation and high humidity delay drying.

Tools / Cleaning

Japan spatula made of hard plastic or stainless steel




[GR\_J1\_1]  
Cleaning with water directly after use or with Aqua RK-898-Cleaning Concentrate for persistent contamination.



---

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



---

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.