



Solvent Colorant

Colour concentrate for tinting solvent-based coating materials using suitable dispensing equipment

Colour	Availability				
	Quantity per pallet	400	500	96	96
	Size / Quantity	1 l	1 l	2 x 5 l	2 x 5 l
	Type of container	Plastic bucket	Plastic bucket	Plastic bucket	Plastic bucket
	Container code	01	01	05	05
	Art. no.				
SOLVENT - 1916 TRANS YELLOW	3693	■		■	
SOLVENT - 2817 TRANS RED	3694		■		■

Application rate Colour-specific

Range of use ■ Used in the Remmers Mix batch mixing systems to tint solvent-based base materials
 ■ For use by professionals



Property profile ■ Very good light-fastness
 ■ High colour accuracy
 ■ High yield


Directions Homogenise well before use, ideally automatically.

Tips on use The contents are only suitable for tinting specially selected base materials. Do not use as a ready-to-apply coating. The product dries quickly in air, therefore the container must always be fully emptied when filling the dispensing system.
 ■ Thinning
 Ready to use

Notes Safety data sheet available on request.

Tools / Cleaning Clean tools immediately after use with Aqua-100 & Solvent-200 Cleaner

Storage / Shelf life If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.
 Avoid storing in high temperatures and direct sunlight.



Safety data / Regulations For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.