



## Aqua H-480 Hardener

Isocyanate for hardening Aqua varnishes

Availability			
Quantity per pallet	880	220	
Size / Quantity	0,5 l	2 l	
Type of container	Tin canister	Tin canister	
Container code	84	02	
Art. no.	3806	■	■

Application rate See instructions for the varnish component

Range of use



- In 2K Aqua varnishes:  
Aqua 2DS-450-2K Diamond Seal  
Aqua 2HL-411/90 High Gloss Varnish
- For use by professionals

Property profile



- Lightfast
- Easy to mix using the Remmers Patent Dispenser

Characteristic data of the product


Binder	Aliphatic polyisocyanate
Density (20 °C)	Approx. 1.103 g/cm <sup>3</sup>
Runout time s in DIN 4 cup	Approx. 52
Odour	Characteristic

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- Aqua 2DS-450-2K Diamond Seal (3869)
- Aqua 2HL-411/90-2K High Gloss Varnish (3872)

Directions



- Conditions for use  
Temperature of the material, air and substrate: from min. +15 °C to max. +25 °C.

Please refer to the Technical Data Sheet for the varnish component for information on the mixing ratio and application instructions.  
Add hardener while stirring and homogenise the mixture for at least 2 minutes using the Remmers Patent Dispenser.  
Seal opened containers well and use contents as soon as possible.  
Mixed material residues must not be allowed to cure in closed containers.

Tips on use

- Thinning  
Ready to use

Notes

Please refer to the relevant test reports/certificates and the Technical Data Sheet for information on certified products and configurations.

Tools / Cleaning




Remmers Patent Dispenser  
Clean tools with water or Aqua RK-898 Cleaning Concentrate immediately after use.  
Ensure that any residue from cleaning is disposed of correctly.



---

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 6 months.



---

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.