



## ULM-822 Universal Light Stabiliser

Optimum protection of light-coloured wood against premature visual changes due to UV radiation


Availability	
Quantity per pallet	432
Size / Quantity	
Type of container	Tin canister
Container code	01
Art. no.	
3824	■

### Range of use



- Especially suited to light and light stained woods: oak, maple, ash, birch, spruce, pine
- Can be used with all transparent Aqua, NC and PUR varnishes
- Can be used in base coats and top coats
- For use by professionals

### Property profile



- Effective protection thanks to broad-spectrum UV absorption by the selected absorbers


### Additional information

- [Sustainability data sheet](#)

### Possible system products

- [Aqua SL-418 Finish \(5310\)](#)
- [Aqua NEL-419/05 Natural Effect Varnish \(5309\)](#)
- [Aqua TL-412 Stair Varnish \(2372\)](#)
- [Aqua NTL-420/05 Natural Effect Stair Varnish \(3221\)](#)
- [Aqua 2SL-452 2K Finish \(5501\)](#)
- [Aqua 2HL-411/90-2K High Gloss Varnish \(3872\)](#)
- [Aqua PL-413 Parquet Varnish \(2374\)](#)
- [PUR SL-210 Finish \(2005\)](#)

### Production of the mixture



#### Mixing ratio

Add 2-3% to the ready-to-use varnish

Stir well before using.

Using the Patent Dispenser, work into the coating material while stirring.

To achieve optimum UV protection, it is recommended to use ULM 822 in both the base coat and the top coat.

### Directions

#### Conditions for use


See the Technical Data Sheet for the coating material used.

Seal opened containers well and use contents as soon as possible.

### Notes

Under the influence of UV light, exclusion of light (dark yellowing), heat or individual wood changes, the appearance of wood can change over the long term. Alternatively or in addition, pigment-based stains, e.g. Aqua KB-004, can minimise colour changes.

### Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.