




Aqua NK-004-Nuancierkonzentrat

Colour	Availability	
	Quantity per pallet	288
	Size / Quantity	1 l
	Type of container	Plastic bottle
	Container code	01
	Art. no.	
black P	3847	■
white P	3850	■
special colours	3764	■

Range of use



- Concentrate for nuancing water-based wood varnishes and stains
- For use by professionals

Property profile




- Highly concentrated pigment preparations
- Lightfast

Possible system products

- Aqua KB-004 Compact Stain (3840)
- Aqua TL-412 Stair Varnish (2372)

Directions



- Conditions for use
Temperature of the material, air and substrate: from min. +18 °C to max. +25 °C.

Stir well.
Homogenise by stirring with the system product.
Seal opened containers well and use contents as soon as possible.


Notes

Before coating technically modified woods and wood-based materials, apply the coating to a trial surface and conduct a suitability test on the desired area of use.

Tools / Cleaning

Clean tools with water or Aqua RK-898 Cleaning Concentrate immediately after use.
Ensure that any residue from cleaning is disposed of correctly.

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal



Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.