



MB PUReactive P-1


1K primer for plastic and elastomer sheets

Availability	
Quantity per pallet	360
Size / Quantity	
Type of container	Tin canister
Container code	01
Art. no.	
4150	■

Application rate Approx. 75 ml/m²



Range of use ■ Primer for plastic and elastomer sheets



Property profile ■ Ready to use
 ■ Can be overcoated after 15 minutes
 ■ Quick-drying
 ■ Optimum adhesion on a wide range of substrates
 ■ Good self-adhesion

Characteristic data of the product	Specific weight	0.75 g/cm ³
	Consistency	liquid
	Colour	slightly yellowish


The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products > MB PUReactive (3003)
 > MB PUReactive TX (2980)
 > MB PUReactive+ (2982)
 > Thinner V 103 (5699)

Preparation ■ Substrate requirements
 The substrate must be level, clean, dust-free and stable, and free of oil, grease and release agents.
 ■ Substrate preparation
 Clean substrate with Thinner V103.

Production of the mixture ■ Mixing
 Shake vigorously before use

Directions ■ Conditions for use
 Temperature of the material, air and substrate: from min. +5 °C to max. +40 °C.
 Low temperatures will extend the hardening time while high temperatures will shorten it.
 Apply the material using a suitable tool.
 Subsequent application of the liquid waterproofing must take place within the specified time frame.





If kept in storage for long periods, or if dirt accumulates in the meantime, clean and prime surfaces again.

Tips on use

A suitability and compatibility test must always be conducted on unknown materials.

- Flash-off time
min. 15 minutes, max. 4 hours (20 °C/50% RH)

Notes

The applicable regulations and legal requirements must be observed.
The relevant test certificates must be observed when planning and carrying out work.
Always set up a trial area/trial areas first.
Use only outdoors or in a well-ventilated area.

Tools / Cleaning

Paintbrush




Clean tools immediately after use with V 103.

Remmers tools

- [Flächenstreicher \(4540\)](#)
- [Heizkörperpinsel \(4541\)](#)

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.