



# Adolit Colour Concentrate (BQ)

Aqueous colour concentrate for uniform wood staining

Colour	Availability	
	Quantity per pallet	24
	Size / Quantity	25 kg
	Type of container	Plastic canister
	Container code	25
	Art. no.	
special colours*	4161	■
*Minimum order quantity 25 kg		

**Application rate** Add 0.3 - 0.5% to the prepared preservative solution depending on the desired colour intensity

**Range of use**



- For adding colour to structural and garden timber during dipping, trough processing and vacuum pressure treatment
- For use by professionals

**Property profile**



- No unwanted settling of the water-soluble colourant
- Intensive pigmentation
- Water-dilutable
- Limited light-fastness

**Characteristic data of the product**

Density (20 °C)                      Approx. 1.07 - 1.1 g/cm<sup>3</sup>

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

**Possible system products**

- **Adolit BQ 20\* (2552)**
- **Adolit BQ 30\* (2565)**

\*Use biocidal products carefully.  
Always read the label and product information before use.

**Directions**



- **Conditions for use**  
Temperature of the material, air and substrate: min. +5 °C.

Depending on the desired colour intensity, add 0.3 - 0.5% of the product to the prepared preservative solution while stirring continuously.

Seal opened containers well and use contents as soon as possible.



**Tips on use**

Before installing exterior wood, the fixing time required for the salts must be observed so that colour components that have not completely dried do not release moisture. Wood that has been coloured with this product should not be used in areas where abrasion or weathering could cause the colour to transfer onto render, light brickwork, plaster or clothing.

**Tools / Cleaning**


Dipping tank or open tank impregnation system



Clean tools immediately after use with water. Ensure that any residue from cleaning is disposed of correctly.

**Storage / Shelf life**

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.