



Quartz 07/12 DF

Fire-dried quartz mix

Availability	
Quantity per pallet	40
Size / Quantity	25 kg
Type of container	Paper bag
Container code	25
Art. no.	
4407	

Application rate	Depending on range of use (please see Technical Data Sheet of each binder)	
Range of use	■ Blinding sand for Remmers systems	
Property profile	■ Washed ■ Fire-dried ■ Dust-free	
Characteristic data of the	Grain density	2.65 g/cm ³
product	Form	Tight
	Particle size	Approx. 0.7 - 1.2 mm
	The values stated represe product specifications.	ent typical characteristic data of the product and are not to be understood as bindin
Application examples	■ Blinding material Generously and evenly broadcast an excess of the material into a suitable Remmers coating while it is still wet. Remove any loose, surplus sand after hardening.	
Notes	The max. degree of filling depends on the binder used, the layer thickness and the conditions on the construction site. Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.	



Storage / Shelf life	Unlimited if stored dry.	
Safety data / Regulations	Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.	
Personal protective equipment	This information can be obtained from the current Safety Data Sheets and/or the relevant professional associations.	

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.