



Tape VF 250 EC large

High-grade premium sealing tape made from nitrile rubber with double-sided non-woven coating

Colour	Availability	
	Quantity per pallet	220
	Size / Quantity	2 x
	Type of container	Carton
	Container code	01
	Art. no.	
blue	4802	■

Application rate As required



Range of use

- For use in exterior areas
- Waterproofing elements at ground level



Property profile

- Highly flexible
- High expansion capability and elastic recovery
- Special non-woven fabric coating
- Alkali-resistant

Characteristic data of the product

Dimensions	height: 50 cm width: 25 cm per side depth: 10 cm
Temperature resistance	-20 °C to +90 °C
Thickness	0.9 mm
Water impermeability	approx. 3.0 bar
Elongation at break	longitudinal: 137% transverse: 175%
Maximum tensile strength	longitudinal: 6.44 N/mm ² transverse: 4.26 N/mm ²

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- [MB 2K \(3014\)](#)
- [WP Flex 1K \(0445\)](#)

Preparation

- Substrate requirements
Load bearing, clean and dust-free.
- Substrate preparation
Remove projecting seams and mortar remains.
Remove gravel packets and fill cavities.
Clean non-mineral substrates until they are free from residues and degrease; roughen if necessary.
Create a scratch coat of waterproofing material on mineral and roughened substrates.
Refer to the current Technical Data Sheet for detailed information on the single products.



Directions



Apply waterproofing material as contact layer, work in Water Stop over the entire surface.
Depending on the waterproofing product used, the 2nd and 3rd layer of waterproofing is applied over the entire surface.

Tips on use

The permissible application temperatures depend on the product properties of the waterproofing products used.
Apply the waterproofing material crosswise in relation to the tape. The tape must not be damaged.

Notes

The current technical regulations must be observed.
Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.
Always set up a trial area/trial areas first.

Tools / Cleaning




For cutting: scissors or knife
For waterproofing: roller, wide brush or scraper

Clean tools with water while the material is still fresh.

Remmers tools

- Profile Trowel (5047)
- Rundkelle (4114)
- Waschboy-Set (4978)
- Schwambrett rot (4935)
- Schwambrett gelb (4936)
- Viskose Reinigungsschwamm (4133)
- Rollerbügel (4449)
- Epoxy Roller (5045)
- Heizkörperpinsel (4541)

Storage / Shelf life



Virtually unlimited when stored dry at room temperature and protected from direct sunlight.

Disposal

The product must be disposed of in accordance with the official regulations.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.