



Tape VF 250 XA

High-quality premium sealing tape with a non-woven coating on an NBR base with 30 mm self-adhesive strips

Availability	
Quantity per pallet	600
Size / Quantity	
Type of container	Roll
Container code	01
Art. no.	
4803	■

Range of use



- Interior and exterior use
- Connection and integration of flexible polymer-modified thick coatings with non-mineral building materials and connection areas such as plastic, metal and wood
- Plinth waterproofing
- Waterproofing in a bond

Property profile

- Flexible
- 30 mm self-adhesive strip with high adhesive strength
- Special non-woven fabric coating


Possible system products

- MB 2K (3014)
- WP Flex 1K (0445)
- Remmers PMBCs

Preparation

- Substrate requirements
Clean, dust-free and capable of supporting a load.
- Substrate preparation
Remove projecting seams and mortar remains.
Remove gravel packets and fill cavities.
Clean non-mineral substrates until they are free from residues and degrease; roughen if necessary.
Create a scratch coat of waterproofing material on mineral and roughened substrates.
Refer to the current Technical Data Sheet for detailed information on the single products.

Directions



Fix the joint tape to the prepared substrate with the self-adhesive strip.
Apply waterproofing material as contact layer, work in Water Stop over the entire surface.
In corner areas, Interior Corner VF and Exterior Corner VF are placed so that they overlap the water stop.
In areas where pipes pass through walls, Wall Gasket VF or a shaped piece made of Water Stop VF 500 can be used.
Depending on the waterproofing product used, the 2nd and 3rd layer of waterproofing is applied over the entire surface.

Notes

The current technical regulations must be observed.
Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.
Always set up a trial area/trial areas first.

Tools / Cleaning

Clean tools with water while the material is still fresh.




- Remmers tools
- Profile Trowel (5047)
 - Rundkelle (4114)



Storage / Shelf life

Virtually unlimited when stored dry at room temperature and protected from direct sunlight.



Disposal

The product must be disposed of in accordance with the official regulations.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.