



Tape B 240 E / Tape B 240

Water stop for waterproofing building expansion joints

Type/Name	Dimensions (length x breadth)	Availability		
		Quantity per pallet	140	24
		Size / Quantity	7 m	30 m
		Type of container	Roll	Roll
		Container code	01	01
		Art. no.		
Tape B 240 E	7 m x 240 mm (with end pieces)	4806	■	
Tape B 240	30 m x 240 mm	4813		■

Application rate According to needs

Range of use



- For use in exterior areas
- Waterproofing building expansion joints
- Waterproofing construction joints and joints with controlled cracks
- Can be embedded in MB 2K

Property profile

- Flexible
- Provides permanent waterproofing
- Compatible with bitumen
- Resistant to cold

Characteristic data of the product

Transverse tensile strength acc. to DIN 53504	> 5.5 N/mm ²
Transverse elongation at break acc. to DIN 53504	> 312%
Longitudinal tensile strength acc. to DIN 53504	> 5.3 N/mm ²
Longitudinal elongation at break acc. to DIN 53504	> 138%

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Additional information > [Special agreement - Waterproofing of building separation joints on continuous floor slabs](#)

Possible system products > [MB 2K \(3014\)](#)

Preparation

- **Substrate requirements**
Clean, dust-free and capable of supporting a load.
- **Substrate preparation**
Remove projecting seams and mortar remains.
Remove gravel packets and fill cavities.
Refer to the current Technical Data Sheet for detailed information on the single products.

Directions

Apply contact layer to 20 cm on both sides of the joint.
Embed the joint tape.
Apply subsequent waterproofing layers min. 10 cm beyond the joint tape.
Keep the marked expansion zone clear.



Tips on use

The permissible application temperatures depend on the product properties of the waterproofing products used.


Notes

Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately.

The relevant test certificates must be observed when planning and carrying out work.

Storage / Shelf life

Virtually unlimited when stored dry at room temperature and protected from direct sunlight.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

The product must be disposed of in accordance with the official regulations.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.