



## Tape F

Non-woven reinforcement tape for 1K multifunctional building waterproofing

Type/Name	Availability			
	Quantity per pallet	120	150	150
	<b>Size / Quantity</b>	<b>50 m</b>	<b>20 pcs</b>	<b>20 pcs</b>
	Type of container	Roll	Bag	Bag
	Container code	01	01	01
	<b>Art. no.</b>			
TAPE F-120	4822	■		
TAPE F-IC	4824		■	
TAPE F-EC	4825			■

**Application rate** According to needs



**Range of use** ■ Non-woven joint tape for MB 1K rapid

**Property profile** ■ Surface weight approx. 110 g/m<sup>2</sup>

**Characteristic data of the product**

Weight	Approx. 110 g/m <sup>2</sup>
Composition	Fibre composition: PES
Colour	White

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

**Possible system products** > **MB 1K rapid (0851)**

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.