



Power Protect First-Aid-Sheet

Sheet for use in the system with the Power Protect First-Aid-Gel

Type/Name	Availability	
	Quantity per pallet	2100
	Size / Quantity	10 pcs
	Container code	01
	Art. no.	
2 x 1 m	4956	■

Application rate Depending on the application



Range of use ■ Special film for placing on the Power Protect First-Aid Gel



Property profile

- Prevents spores from being emitted into the ambient air
- Conductive
- Alcohol-resistant
- Anti-static 3%

Characteristic data of the product	Colour	clear
	Thickness	100 µm
[pk_an_oberflaechenwiderstand]	10 ⁹ to 10 ¹¹ Ohm	

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- **Power Protect First-Aid Gel* (0684)**
- **Power Protect First-Aid Kit (0679)**

*Use biocidal products carefully.
Always read the label and product information before use.

Directions

Apply the material.
Apply the film tightly and tape down the edges with adhesive tape.
Using a suitable tool, spread the material out evenly underneath the film.




Notes

We cannot accept any liability for the service life of the anti-static agents, because these are a migrating additive. Surface resistance values are dependent on storage, handling and humidity. Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.

Storage / Shelf life

Keep out of reach of children. Store in unopened original containers in a cool, dry place. Protect from direct sunlight and frost. Store in a well ventilated area. If these requirements are met, the product shelf life is at least 24 months. Do not smoke in areas where the product is stored.





Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.