



Tape XA 100/XA 250

- Water Stop SK 10/Water Stop SK 25 -

Highly elastic, self-adhesive butyl rubber waterproofing tape on polypropylene non-woven fabric

| Type/Name | Availability | | |
|-------------|---------------------|--------|--------|
| | Quantity per pallet | 105 | 120 |
| | Size / Quantity | | |
| | Type of container | Carton | Carton |
| | Container code | 01 | 01 |
| | Art. no. | | |
| Tape XA 250 | 5003 | ■ | |
| Tape XA 100 | 5017 | | ■ |

Application rate

According to needs



Range of use



- Interior and exterior use
- Connection and integration of MB 2K, MB TX 2K, Betofix OS 5b+; PMBCs and flexible, mineral waterproofing slurries to non-mineral building materials and connection areas such as plastic, metal and wood.

Property profile

- Flexible
- High adhesive strength
- Special non-woven fabric coating
- Watertight

Characteristic data of the product

| | |
|----------------------|--|
| Thickness | XA 100 = approx. 0.7 mm XA 250 = approx. 0.8 mm |
| Water impermeability | Approx. 1.0 bar |
| Elongation at break | Lengthwise = approx. 165% after dry storage, 181 % after storage in 3 % potassium hydroxide solution |
| Total width | XA 100 = 100 mm XA 250 = 250 mm |
| Colour | blue |



The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates > [Prüfbericht 8552/18 \(PG-AIV-F\) Säurefließner-Vereinigung E.V.](#)

Possible system products

- > [MB 2K \(3014\)](#)
- > [WP Flex 1K \(0445\)](#)
- > [Remmers PMBCs](#)

Preparation

- **Substrate requirements**
Load-bearing, dry, clean and dust-free.
- **Substrate preparation**
Remove projecting seams and mortar remains.
Remove gravel packets and fill cavities.
Clean non-mineral substrates until they are free from residues and degrease; roughen if necessary.
Create a scratch coat of waterproofing material on mineral and roughened substrates.
Refer to the current Technical Data Sheet for detailed information on the single products.

Directions



Affix directly to the prepared substrate.
In corner areas, notch the tape and stick it down so that it is overlapping.
Apply the waterproofing material over the entire surface of the tape.
Carefully loosen partial adhesions of the silicone film, then continue to peel off the film.

Tips on use

The permissible application temperatures depend on the product properties of the waterproofing products used.
The joint tape must not be damaged when working over it.

Notes

The current technical regulations must be observed.
Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.
Always set up a trial area/trial areas first.

Tools / Cleaning



For cutting: scissors or knife
For waterproofing: roller, wide brush, filler knife

Clean tools with water while the material is still fresh.

Storage / Shelf life



Virtually unlimited when stored dry at room temperature and protected from direct sunlight.
Roller must be stored upright to prevent pressure points.

Disposal

The product must be disposed of in accordance with the official regulations.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.