



V-899 Thinner

Rapid thinning and cleaning of tools

Availability	
Quantity per pallet	50
Size / Quantity	
Type of container	Tin canister
Container code	10
Art. no.	
5143	■

Range of use



- Thinner for 2-component PUR products
- Adjusting NC coatings (spraying without wiping)
- Cleaning tools
- For use by professionals

Property profile



- Free of aromatic compounds
- Good cleaning action
- Improved deaeration on coarse-pored woods (e.g. oak, walnut, ash)

Characteristic data of the product

Density (20 °C) Approx. 0.80 g/cm³

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- [NC HB-005 Wood Stain \(3826\)](#)
- [PUR-SL-21X Finish](#)

Directions




- Conditions for use
Temperature of the material, air and substrate: from min. +18 °C to max. +25 °C.

Tools / Cleaning

Ensure that any residue from cleaning is disposed of correctly.

Storage / Shelf life



At least 36 months in unopened, original containers stored cool, dry and protected from frost.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.