



rotec spacer ring



Availability	
Quantity per pallet	5555
Size / Quantity	
	5 pcs
Container code	01
Art. no.	
5265	■

Range of use

- Accessories for the pressure blasting equipment from Schmidt Sandstrahltechnik GmbH (www.schmidt-sandstrahltechnik.de) **VARIO PRIMUS KE 25** or **45 litres**, as well as other blasting equipment

Property profile

- Material: EPDM
- Inner diameter: approx. 17 mm
- Outer diameter: approx. 27 mm
- Length: approx. 27 mm
- Temperature range: approx. -40 to +100 °C
- Hardness (Shore A) DIN ISO 7619-1: approx. 50 ° +/- 5 Shore A
- Tear strength DIN 53504: approx. 8 MPa
- Tear strength DIN 53504: approx. 500%

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.