



## Aqua OZA-90 Open Time Additive

Drying inhibitor for water-based stains, coatings and varnishes

Availability	
Quantity per pallet	288
Size / Quantity	
Type of container	Plastic bottle
Container code	01
Art. no.	
5320	■

### Range of use



- Extension of the open time for water-based coating systems
- Particularly suitable for brush and roller application
- For preventing streaking at high temperatures and/or low relative humidity
- Large surface areas
- For use by professionals

### Property profile

- Inhibits drying
- Optimises flow
- Enables streak-free application
- Reduces viscosity

### Possible system products

- Aqua OVL-49/tm Grey Stain Oil <sup>[eco]</sup> (3212)
- Aqua MSL-45/sm Medium Build Stain UV+ (7130)
- Aqua OML-48/tm Medium Build Oil Stain <sup>[eco]</sup> (7710)
- Aqua DSL-55 High Build Stain PU (7220)
- Aqua NEL-56/tm Natural Effect Varnish (7151)
- Aqua VL-66/sm-Venti Coat 3in1 (7090)
- Rofalin Acrylic (2330)
- Rofalin Acrylic Plus (2329)
- Aqua DL-65 Top PU (7200)
- Aqua OWF-68/tm Weather Protection Oil Woodstain <sup>[eco]</sup> (7740)

### Production of the mixture




Shake well before every use.  
Homogenise by stirring with the system product.

### Notes

The effectiveness depends on the system used.  
Material contains suspended particles in the non-homogenised state. This is not a quality defect.  
Delays the achievement of the final block strength and mechanical resistance values.

### Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for 6 months.  
Use coatings containing additives as quickly as possible.

### Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.