



# Aqua H-484 Hardener

Lightfast isocyanate for curing Aqua varnishes

Availability	
Quantity per pallet	
<b>Size / Quantity</b>	<b>21</b>
Type of container	Tin canister
Container code	02
<b>Art. no.</b>	
5500	■

**Application rate** Add to the varnish in the specified mixing ratio

**Range of use**

- For 2K Aqua varnishes
- For use by professionals

**Property profile**

- Lightfast
- Easy to mix using the Remmers Patent Disperser
- Diisocyanate content < 0.1% by weight, not subject to mandatory training pursuant to EU 2020/1149
- Slow, small increase in the viscosity of the prepared mixtures

Characteristic data of the product	Binder	Aliphatic polyisocyanate
	Density (20 °C)	Approx. 1.09 g/cm <sup>3</sup>
	Runout time s (20° C, DIN 4)	Approx. 30
	Odour	Characteristic

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

**Possible system products**

- [Aqua 2HL-411/90-2K High Gloss Varnish \(3872\)](#)
- [Aqua 2SL-452-2K Finish \(5501\)](#)
- [Aqua 2CL-442-2K Colour Varnish \(5505\)](#)
- [Aqua 2IF-437-2K Sealing Filler \(3216\)](#)

**Production of the mixture**

**Mixing ratio** Add to the varnish in the specified mixing ratio.

Add hardener while stirring and homogenise the mixture.  
Use the Remmers Patent Disperser.

**Directions**

- **Conditions for use**  
Temperature of the material, air and substrate: from min. +18 °C to max. +25 °C.

Seal opened containers well and use contents as soon as possible.  
Mixed material residues must not be allowed to cure in closed containers.

**Tips on use**

- **Thinning**  
Ready to use

**Notes** Please refer to the relevant test reports/certificates and the Technical Data Sheet for information on certified products and configurations.



**Tools / Cleaning**


Remmers Patent Dispenser



Clean tools with cold water or Aqua RK-898 Cleaning Concentrate immediately after use. Ensure that any residue from cleaning is disposed of correctly.

**Storage / Shelf life**

If stored in the unopened original container in a cool, dry place protected from frost, the product will keep for at least 12 months.



**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.