



V 103

Cleaning and thinning agent

Availability			
Quantity per pallet	360	84	
Size / Quantity	1 l	5 l	
Type of container	Tin canister	Tin canister	
Container code	01	05	
Art. no.	5699	■	■

Application rate Dependent on application

Range of use

- Universal solvent for thinning and cleaning reactive resins that have not yet reacted
- Cleaning non-absorbent, non-mineral substrates prior to the use of waterproofing products from the MB PUReactive range

Property profile

- Good cleaning action, in particular for polyurethane-based binders
- Good thinning action, in particular for Epoxy Universal



Characteristic data of the product

Density (20 °C)	approx. 0.9 g/cm ³
Flash point °C	approx. 32 °C

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates > [Datenblatt über Inhaltsstoffe](#)

Notes

Make sure that the area is well ventilated during processing and drying.
Apply to a trial/sample area in an inconspicuous location before use.
Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

Storage / Shelf life Unlimited



Safety data / Regulations For professional users only!
Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

Personal protective equipment Respiratory protection with at least an A/P2 combination filter must be worn during spraying, together with safety goggles. Wear suitable protective gloves and clothing.

Disposal Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Detergents Regulation (EC) No 648/2004 > 30 % methoxyisopropanol, aromatic hydrocarbons



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.