




Directions

For professional users only!



■ **Conditions for use**

Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.

The relative humidity must be between 40% and 80%.

The temperature of the substrate must be at least 3 °C above the dew point temperature during application and curing.

■ **Waiting time (+20 °C)**

Min. 2 to max. 8 hours at 50% relative humidity

Waiting time between coats depends heavily on the humidity. The solvent must be fully evaporated. The substrate must be able to withstand foot traffic, but may still have a slight tack.

Higher temperatures and higher absolute humidity reduce the specified times, while lower temperatures and lower absolute humidity increase them.

Avoid creating thick layers of the material, otherwise there is a risk of foam formation.

Application examples

■ **Roller coating**

Using a microfibre roller, apply a thin, even layer of adhesion promoter crosswise.

Application rate	approx. 0.05 kg/m ²
------------------	--------------------------------

Notes

Unless otherwise specified, all of the values and application rates given above have been determined under laboratory conditions (20 °C) using standard colours. Slight deviations from these values may arise if the product is worked with on site.

The product cures under the influence of humidity. If the layers are too thick, foam may form.

Do not use on old (more than 2 days old) or superficially damaged surfaces (e.g. crackling or heavy chalking).

The substrate must be protected against direct water loads before, during and after coating. If this is not done, the adhesion promoter must be applied again.

Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

Tools / Cleaning

Microfibre roller, paintbrush, mixing equipment




More detailed information can be found in the Remmers Tool Programme.

Clean tools and remove any contamination immediately after use and while fresh using Thinner V 103.

Take suitable protective and waste disposal measures when cleaning.

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



Safety data / Regulations

For professional users only!

Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Declaration of conformity



Remmers GmbH (CE)

Bernhard-Remmers-Str. 13, D – 49624 Lönigen

Remmers (UK) Limited (UKCA)

1 & 2 Garden Suites, Coleshill Manor Campus, Birmingham B46 1DL (GB)

19 (CE); 22 (UKCA)

GBIII 137_2

EN 13813:2002

6062

Synthetic resin screed for use internally in buildings

Reaction to fire:	E _{fl}
Release of corrosive substances:	SR
Wear resistance:	≤ AR 1
Bond strength:	≥ B 1.5
Impact resistance:	≥ IR 4

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.