



## Colorid Collection

Coloured flakes for fully broadcast blinding



Colour	Availability	
	Quantity per pallet	56
	Size / Quantity	10 kg
	Type of container	Carton
	Container code	10
	Art. no.	
Colorid 305 black-anthracite	6227	■
Colorid 315 light grey-white	6237	■
Colorid Mix AF grey-mottled	6224	■
Special colours from 10 kg	6241	■
Special colours available on request. Delivery time 10 working days.		

Application rate      Dependent on application

Range of use      ■ Fully broadcast blinding in Remmers floor coatings  
 ■ Component of systems approved by the German Institute for Structural Engineering (DIBt) for recreation rooms

Property profile      ■ Multicoloured

Characteristic data of the product	Bulk density	0.5 - 1.0 g/cm <sup>3</sup>
	Grain density	2.65 g/cm <sup>3</sup>
	Flake size	medium
	Form	solid

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates      > Test report - Colorid system  
 > Colorid Collection, article numbers  
 > Water vapour diffusion density according to DIN EN ISO 7783 (matt)  
 > Water vapour diffusion density according to DIN EN ISO 7783 (gloss)  
 > Classification report for fire test

Application examples      ■ Blinding material  
 Scatter fully broadcast and evenly into a suitable Remmers coating while it is still wet.

Application rate      approx. 0.5 - 1.0 kg/m<sup>2</sup>

Notes      Protect the blinded coating surface securely with a suitable closed synthetic resin film.  
 Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

Storage / Shelf life      Unlimited if stored dry.



Safety data / Regulations      For professional users only!



---

Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

---

Personal protective equipment	This information can be obtained from the current Safety Data Sheets and/or the relevant professional associations.
-------------------------------	---

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.