



Primer Hydro LC

Primer and bonding layer for Baseplan



| Availability | |
|------------------------|------------------|
| Quantity per pallet | 75 |
| Size / Quantity | 5 l |
| Type of container | Plastic canister |
| Container code | 05 |
| Art. no. | |
| 6359 | ■ |

Application rate Approx. 100-150 ml/m² depending on the substrate
Apply to a large enough trial area to determine the precise amount required.

Range of use

- Interiors
- Primer on non-absorbent substrates, e.g. old ceramic coverings
- Primer on gypsum-based or cement-based mineral substrates



Property profile

- Solvent-free
- Quick drying
- Ready to use
- Excellent adhesion to non-absorbent substrates
- Textured surface for optimum adhesive bonding



Characteristic data of the product

| Appearance | Transparent blue |
|--|------------------|
| The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications. | |

Certificates > [GEV - EMICODE](#)


Possible system products > [Baseplan \(6358\)](#)

Preparation

- **Substrate requirements**
The substrate must be firm, dimensionally stable, capable of bearing loads and free of loose constituents, dust, oil, grease, rubber marks and other substances that could interfere with adhesion.
Before the material is applied, the substrate must not exceed the following max. moisture contents:
 - Heated and unheated cementitious substrates: max. 2.0 CM-%
 - Calcium sulphate based substrates: max. 0.5 CM-%
 - Heated calcium sulphate substrates: max. 0.3 CM-%

Directions

- **Conditions for use**
Observe flash-off times.
- **Waiting time (+20 °C)**
Can be overcoated after approx. 60 minutes



Shake the material and pour onto the surface in portions. Using an epoxy roller, distribute the material evenly and carefully work into the substrate.

Application examples

Absorbent substrates:
Dilute the material with water in a ratio of 1 : 1



Non-absorbent substrates:

Use the material undiluted


Notes The current technical regulations must be observed.
Deviations from applicable regulations must be agreed separately.

Tools / Cleaning Epoxy roller, brush



Clean tools, equipment and any splashed material immediately with water while still fresh.

Storage / Shelf life If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 18 months.
Seal opened containers well and use contents as soon as possible.



Safety data / Regulations For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.