



Historic Kalkspachtel

Colour	Availability	
	Quantity per pallet	32
	Packaging unit	10 kg
	Type of container	Plastic bucket
	Container code	10
	Art. no.	
	6562	■

Range of use

- [AW_SpM_3]
- [AW_SpM_4]



Property profile

- Capillary-active
- [EG_SpM_4]
- [EG_FS_9]
- [EG_FS_10]
- [EG_SpM_5]
- Low-stress
- Good adhesive power
- [EG_SpM_7]



Possible system products

- [Historic Kalkspachtel fein \(6564\)](#)
- [Historic Kalkfarbe \(6569\)](#)
- [Historic Kalkschlämme \(6566\)](#)


Preparation

- **Substrate requirements**
 Dry, clean, free of dust and cracks (except hairline cracks) and capable of supporting a load.
 Free of salts known to be damaging to building materials.
 [U1_NK_1]
- **Substrate preparation**
 Pre-wet the substrate.
 [VA1_RM_30]

 [VA1_RM_28]
 [VA1_RM_29]



Directions



Using a suitable tool, apply the product as a contact layer.

[VA1_SpM_1]

Wait at least 12 hours between coats.

Smooth the surface using a suitable tool.

Finish the surface once set.

Can be sanded once set.

[VA1_M_717]

Tips on use

[U2_FS_2]

[VA2_FS_6]

When coating continuous surfaces, only use materials with the same batch number.

[VA2_FS_8]

[VA2_FS_5]

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.

Notes

Always set up a trial area/trial areas first.

The characteristic data of the product were calculated under laboratory conditions at 20°C and 65% relative humidity.

Low temperatures, poor ventilation and high humidity delay drying.

Deviations from applicable regulations must be agreed separately.


The relevant test certificates must be observed when planning and carrying out work.

Tools / Cleaning



Clean tools, equipment and any splashed material immediately with water while still fresh.

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.