



Color CL Historic

- Historic Lime Paint -
Lime paint without organic binders

Colour	Availability
	Quantity per pallet 32
	Size / Quantity 10 kg
	Type of container Plastic bucket
	Container code 10
	Art. no.
white	6569 ■

Application rate



Approx. 0.2 - 0.25 kg/m² per coat
2 coats required.
Application rates may vary depending on the condition of the surface.
Apply to a large enough trial area to determine the precise amount required.

Range of use



- Porous, mineral building materials in interior areas
- Preservation of historical monuments
- Eco-friendly construction

Property profile



- Capillary-active
- Highly water vapour diffusible
- Good hiding power
- Free from organic binder additives
- Free from solvents and plasticizers
- Free from preservatives
- With a mineral water base
- Does not contain titanium dioxide
- Allergy friendly
- Naturally antiseptic
- Low-stress
- Good adhesive power

Characteristic data of the product

■ On delivery	
Binder	Dispersed white hydrated lime
Density (20 °C)	1.54 g/cm ³
Viscosity	3500 mPa·s
pH value	> 11
■ Once fully cured	
Water vapour permeability (DIN 52615)	S _d < 0.01 m
Water absorption coefficient (DIN 52617)	Substrate-dependent
Colour	White
Degree of gloss	Cloth matt

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- [Color CL Fill Historic \(6566\)](#)
- [CL Fill Q3 Historic \(6562\)](#)
- [CL Fill Q4 Historic \(6564\)](#)




➤ [Remmers cleaning products](#)

Preparation

- **Substrate requirements**
Dry, clean, free of dust and cracks (except hairline cracks) and capable of supporting a load.
Free of salts known to be damaging to building materials.
Absorbent
- **Substrate preparation**
Pre-wet the substrate.
Use Historic Lime Wash to level out any textural unevenness.

Directions



Stir well and apply quickly using a brush or roller.
2 coats required.
Observe a waiting time of at least 24 hours between coats.
To reduce chalking, coated surfaces should be subsequently wetted several times.

Tips on use

Check the absorbency of the substrate on a sufficiently large test area.
To prevent a crust forming, work wet-on-wet in a single operation.
When coating continuous surfaces, only use materials with the same batch number.
The final colour after drying and hardening depends on the absorptive capacity of the substrate, the ambient conditions, processing and subsequent treatment.
Substrates with moisture penetrating from the rear can cause discolouration.
Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.

- **Drying**
Touch-dry: 4 to 6 hours
Recoatable: 24 hours
The characteristic data of the product were calculated under laboratory conditions at 20°C and 65% relative humidity.
Low temperatures, poor ventilation and high humidity delay drying.
- **Thinning**
The material can be diluted with up to 10% water.

Notes

Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.

Tools / Cleaning



Brush, flat brush, lambskin roller

Clean tools, equipment and any splashed material immediately with water while still fresh.

Remmers tools

- [Flächenstreicher \(4540\)](#)
- [Farbrolle FC \(4913\)](#)
- [Rollerbügel \(4449\)](#)
- [Epoxy Roller \(5045\)](#)
- [Heizkörperpinsel \(4541\)](#)

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.