





Personal protective

equipment

Ceramix HS 14

Special hard material

| | Availability | |
|---------------------------|--|-----------|
| | Quantity per pallet | 40 |
| | Size / Quantity | 25 kg |
| | Type of container | Paper bag |
| | Container code | 25 |
| | Art. no. | |
| | 6648 | • |
| | | |
| Range of use | ■ Blinding material in Remmers systems | |
| Property profile | Dust-freeAbrasion resistantGrain size: 1.0 - 1/4 mm | |
| Application examples | ■ Blinding material Generously and evenly broadcast an excess of the material into a suitable Remmers coating while it is still wet. Remove any loose, surplus sand after hardening. | |
| Notes | Colours may vary slightly between batches. Adjustments cannot be made to surfaces that have already been laid. Different grain sizes will always differ slightly in appearance, even if they are the same colour. Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations. | |
| Storage / Shelf life | Unlimited if stored dry. | |
| | | |
| Safety data / Regulations | For professional users only! | |
| | Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet. | |

This information can be obtained from the current Safety Data Sheets and/or the relevant

professional associations.





Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.