



Mica GHL 3/0

Mineral blinding material

Availability	
Quantity per pallet	44
Size / Quantity	
Type of container	Plastic bucket
Container code	03
Art. no.	
6742	■

Application rate Dependent on application

Range of use ■ Targeted blinding for Remmers floor coatings

Property profile ■ Adds surface texture

Characteristic data of the product	Grain density	0.15 - 0.25 g/cm ³
	Form	Flakes
	Particle size	Up to approx. 3 mm

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Application examples ■ Blinding material
For targeted blinding, scatter evenly into suitable Remmers coating while it is still wet.
Note: level of coverage max. 30% in AS/ESD systems.

Application rate	0.01 - 0.05 kg/m ²
------------------	-------------------------------

Notes Max. level of coverage less than 20% when used in dissipative systems.
Use suitable measures to protect furnishings, machinery and neighbouring surfaces.
Wear a dust mask (see Safety Data Sheet).
Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

Storage / Shelf life Unlimited if stored dry.



Safety data / Regulations For professional users only!
Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

Personal protective equipment This information can be obtained from the current Safety Data Sheets and/or the relevant professional associations.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.