



Selectmix SBL DF

Filler mixture with a special aggregate grading curve

Availability		
Quantity per pallet	70	63
Size / Quantity	10 kg	15 kg
Type of container	Paper bag	Paper bag
Container code	10	15
Art. no.		
6751	■	■

Application rate Dependent on application (see Technical Data Sheet for the relevant binder)

Range of use ■ Special filler for suitable Remmers epoxy resin systems

Property profile ■ High degree of filling possible even at low layer thicknesses
 ■ Generates very little dust

Characteristic data of the product


Density	2.5 g/cm ³
Form	Solid
Particle size	up to 0.4 mm

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products > Epoxy BS 4000 (6320)
 > Epoxy UV 100 (6344)
 > Metalufloor (6880)

Notes The max. degree of filling depends on the binder used, the layer thickness and the conditions on the construction site.
 Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.

Storage / Shelf life Unlimited if stored dry.



Safety data / Regulations For professional users only!
 Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

Disposal Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.