Artico Color

Pigment paste

Colour	Availability	
	Quantity per pallet	50
	Size / Quantity	**1,5 kg**
	Type of container	Tin bucket
	Container code	02
	Art. no.	
Special colours from 1.5 kg	6767	■

Application rate

Approx. 0.13 kg/m² of prepared mixture (1.5 kg Artico Color with 2.5 kg binder)

Range of use

- Pigment paste for PUR Top M Plus 2K and PUR Top TX

Property profile

- Highly concentrated
- Pre-assembled

Possible system products

- PUR Top TX (6330)
- PUR Top M Plus 2K (6736)

Production of the mixture

- Mixing

For pigmentation applications on the construction site, pour 2.5 kg of binder into the container of Artico Color paste and mix thoroughly. For further details, see the Technical Data Sheet of the binder.

Storage / Shelf life



If stored in the unopened original container and kept cool, dry and protected from frost, the product will keep for at least 3 months.

Safety data / Regulations

For professional users only!

Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.