



# Aqua MR-91 Multi-Purpose Cleaner

Water-based cleaner for plastics and metals

|                        |                |
|------------------------|----------------|
| <b>Availability</b>    |                |
| Quantity per pallet    | 864            |
| <b>Size / Quantity</b> |                |
| Type of container      | Plastic bottle |
| Container code         | 01             |
| <b>Art. no.</b>        |                |
| 7259                   | ■              |

Application rate As needed




Range of use



- Preparing plastic and metal substrates
- Rigid plastics: rigid PVC, PUR, acrylic, melamine resin & HPL
- Metal components: e.g. fences, frames, railing, doors, down pipe, trapezoidal metal sheet, metal shuttering, radiators
- Removing grime, dirt incrustation, dust, oil and grease deposits
- Not suitable for ferrous metals
- For use by professionals

Property profile



- Good cleaning action
- Highly washing active
- Perfect for substrate pre-treatment
- Solvent-free and environmentally friendly
- Biodegradable

Characteristic data of the product

|            |                |
|------------|----------------|
| pH value   | Approx. 12     |
| Appearance | Clear solution |

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products

- [Aqua ML-69/sm 3 in 1 Multi-Purpose Varnish \(7250\)](#)
- [Aqua AG-26 Universal Primer \(7147\)](#)
- [Aqua AG-28 2K Universal Primer \(7160\)](#)
- [AG-20 Universal Primer \(7150\)](#)

Preparation

- Substrate preparation  
Mechanically remove coarse soiling.  
Set up a trial area to determine the cleaning effect.

Directions



Apply the material using a non-woven abrasive or an abrasive sponge.  
Wash off thoroughly.  
Remove cleaning agent until no residues remain.  
If needed, repeat the application.

Tips on use

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.

Tools / Cleaning

Non-woven abrasive, abrasive sponge



---

Clean tools immediately after use with water.

---

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



---

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.  
Any material that is contaminated after application must be disposed of in accordance with the applicable regulations.

---

Detergents Regulation (EC) No 648/2004

< 5% anionic surfactants

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.