



# Silicone Primer P

Primer for silicone sealants

Availability	
Quantity per pallet	800
Packaging unit	250 ml
Container code	83
Art. no.	
7270	■

**Application rate**                      Approx. 10 ml/running metre on average for both joint sides  
 The application rate depends on the condition of the substrate.  
 Apply to a large enough trial area to determine the precise amount required.

**Range of use**                            ■ Primer in joint formation areas  
    ■ Especially for use outdoors  
    ■ For areas subjected to heavy mechanical loads




**Property profile**                        ■ Quick-drying  
    ■ Optimum adhesion on a wide range of substrates  
    ■ Good self-adhesion

**Possible system products**        > [MultiSil \(7380\)](#)  
    > [MultiSil NUW \(7525\)](#)

**Preparation**                             ■ **Substrate requirements**  
 Joint sides must be clean, dry, free from grease and capable of bearing a load.

**Directions**                                ■ **Conditions for use**  
 Temperature of the material, air and substrate: from min. +5 °C to max. +40 °C  
 Apply the material using a suitable tool.  
 Apply the next material within the specified reaction time (Δ min/max).



**Tips on use**                                Low temperatures increase the setting time, while high temperatures decrease it.  
 Do not use on PMMA (e.g. Plexiglas).  
 When working on plastics, test first on an inconspicuous place.

■ **Flash-off time**  
 Min. 15 minutes, max. 120 minutes (20 °C/50% RH)



**Notes**

The applicable regulations and legal requirements must be observed.  
 The relevant test certificates must be observed when planning and carrying out work.  
 Always set up a trial area/trial areas first.  
 Use only outdoors or in a well-ventilated area.

**Tools / Cleaning**


Brush



Clean tools immediately after use with V 101 Thinner.

**Storage / Shelf life**

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.