



Underwater Primer


Two-component primer for joint sealants in permanently wet areas

Availability	
Quantity per pallet	240
Packaging unit	200 g
Container code	83
Art. no.	
7450	■

Application rate According to needs
Apply to a large enough trial area to determine the precise amount required.

Range of use

- Joints that are permanently wet or underwater
- On highly porous substrates
- Primer for silicone and PUR sealants



Property profile

- Resistant to permanent water exposure
- Quick-drying
- Optimum adhesion on many substrates

Possible system products

- [MultiSil NUW \(7525\)](#)
- [PU AW \(7630\)](#)
- [AW Pouring Compound 2K \(7641\)](#)


Preparation

- **Substrate requirements**
Joint sides must be clean, dry, free from grease and capable of bearing a load.

Directions

- **Conditions for use**
Temperature of the material, surroundings and substrate: from min. +5 °C to max. +40 °C

Using a suitable mixer, mix the material intensively for approx. 3-5 minutes until homogeneous.
Apply the material using a suitable tool.
Apply the next material within the specified reaction time (Δ min/max).



Tips on use

Low temperatures increase the setting time, while high temperatures decrease it.
Do not use on PMMA (e.g. Plexiglas).
When working on plastics, test first on an inconspicuous place.
Take appropriate measures to protect adjacent building elements and materials that



should not come into contact with the product.

■ **Flash-off time**

Min. 2 hours, max. 8 hours (20 °C/50% RH)

Notes

The applicable regulations and legal requirements must be observed.
 The relevant test certificates must be observed when planning and carrying out work.
 Always set up a trial area/trial areas first.
 Use only outdoors or in a well-ventilated area.


Tools / Cleaning

Suitable stirrer, brush

Clean tools immediately after use with V 101 Thinner.

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.